



Fan-assisted ventilated cooling system

Self closing doors

Fin block evaporator

Solid construction

Strong industrial shelving

Pressure injected foam insulation

Integral locks fitted as standard

Electronic temperature controller

Full length double glazed glass door

Fully adjustable shelves every 11mm

Hammered aluminium inner liner

Interior illumination

R134a refrigerant

Modern, stylish and durable door frames

Technical Specifications

MODEL	C5 single door bottle chiller	MODEL	C8 compact double door chiller	MODEL	C10 MEGA double door chiller
CAPACITY		CAPACITY		CAPACITY	
Nett Total/Litres	420	Nett Total/Litres	800	Nett Total/Litres	840
PERFORMANCE		PERFORMANCE		PERFORMANCE	
Power Input watts	TBC	Power Input watts	TBC	Power Input watts	TBC
Energy Consumption Kwh/24h	3.3	Energy Consumption Kwh/24h	3.8	Energy Consumption Kwh/24h	4.5
Temperature Range	0°-10°C	Temperature Range	0°-10°C	Temperature Range	0°-10°C
FEATURES		FEATURES		FEATURES	
Temp. Control	Electronic	Temp. Control	Electronic	Temp. Control	Electronic
Shelves	5	Shelves	5	Shelves	5
Plug	UK	Plug	UK	Plug	UK
Refrigerant	R134a	Refrigerant	R134a	Refrigerant	R134a
DIMENSIONS		DIMENSIONS		DIMENSIONS	
Net HxWxD	2050x600x690	Net HxWxD	2050x1000x690	Net HxWxD	2050x1200x690
Weight Nett	100.5	Weight Nett	138	Weight Nett	153

© 2007 Husky Group Ltd. * Community Designs applied for. Husky Group reserve the right to change specifications at any time without notice