



features

- **ULTRA** fast pulldown times
- **ULTRA** clear display!
- Self closing doors with locks as standard
- C8HY and C10HY also available with sliding doors
- Fin block evaporator and condenser
- Solid construction
- EBM fan motor
- Pressure injected foam insulation
- Electronic temperature controller
- Full length double glazed door(s)
- Industrial shelves adjustable every 10mm
- Fitted castors, front two with brake
- Full length illumination
- Auto defrost with self-evaporating drip tray

ALSO AVAILABLE AS 'ZUB ZERO' FROSTERS

options (available at additional cost)

- R290 refrigerant
- Danfoss compressor
- 'ZubZero' froster specification

Technical Specifications

MODEL	HUS-C5-HY single door bottle chiller	MODEL	HUS-C8-HY compact double door chiller	MODEL	HUS-C10-HY MEGA double door chiller
CAPACITY		CAPACITY		CAPACITY	
Nett Total/Litres	420	Nett Total/Litres	800	Nett Total/Litres	880
PERFORMANCE		PERFORMANCE		PERFORMANCE	
Energy Consumption Kwh/24h	3.48	Energy Consumption Kwh/24h	4	Energy Consumption Kwh/24h	4.50
Temperature Range	0°-10°C	Temperature Range	0°-10°C	Temperature Range	0°-10°C
FEATURES		FEATURES		FEATURES	
Temp. Control	Electronic	Temp. Control	Electronic	Temp. Control	Electronic
Shelves	5	Shelves	5	Shelves	5
Plug	UK	Plug	UK	Plug	UK
Refrigerant	R134a	Refrigerant	R134a	Refrigerant	R134a
DIMENSIONS		DIMENSIONS		DIMENSIONS	
Net HxWxD	1998x600x690	Net HxWxD	1998x1000x690	Net HxWxD	1998x1200x690
Weight Nett	100.5	Weight Nett	147	Weight Nett	170
Container Qty 40'HC	54	Container Qty 40'HC	33	Container Qty 40'HC	27

© 2010 Husky Group of Companies. * Community Designs applied for. Husky reserve the right to change specifications at any time without notice